



TD-9462S4-C-E

6MP Dual Illumination Water-proof Bullet Network Camera



- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution: 6MP (3200 × 1800)
- Auto day/night switch
- 3D DNR, HWDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- Up to 40m white light view distance; Up to 50m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support P2P function
- Support SMD
- Support line crossing detection, region intrusion detection, abandoned/missing object detection, video exception detection



en.tvt.net.cn


For more information, please visit our website

SPECIFICATIONS

Specifications	Model	TD-9462S4-C-E
Camera		
Image Sensor	1 / 2.5 "CMOS	
Image Size	3200×1800	
Electronic Shutter	1 / 4 s ~ 1 / 100000 s	
Iris Type	Fixed Iris	
Min. Illumination	0.002 lux, AGC ON; 0 lux with illumination on	
Lens	2.8mm@F1.6, Horizontal FoV: 104°; Vertical FoV:55°;Diagonal FoV:128° 3.6mm@F1.6, Horizontal FoV:78°; Vertical FoV:38°;Diagonal FoV:94°	2.8~12mm@F1.6, H.FoV: 108°~36°; V.Fov: 57°~20°;D.FoV: 129°~42°
	Focus	Fixed Motorized
Lens Mount	M12	Φ14
Day&Night	ICR	
Wide Dynamic Range	120dB	
BLC	Yes	
HLC	Yes	
Digital NR	Yes	
S/N Ratio	≥50dB	
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°	
Image		
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub /Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG	
H.265 Compression Standard	Main Profile@Leve4.1 High Tier	
Resolution	6MP (3200 × 1800), 4MP (2688 × 1520), 1080P (1920 × 1080), 720P (1280 × 720), D1, VGA (640 × 480), 480 × 240, CIF	
Main Stream	60Hz: 6MP(1~20fps) /4MP/1080P (1~30fps) 50Hz: 6MP(1~20fps) /4MP/1080P (1~25fps)	
Sub Stream	720P/D1/VGA/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)	
Third Stream	D1/480 × 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)	
Bit Rate	64 Kbps ~8Mbps	
Bit Rate Type	VBR / CBR	
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser	
Audio Compression	G711A/U	
ROI	Each ROI to be configured separately	
Interfaces		
Network	RJ45	
Video Output	No	
Audio	1CH audio input; 1CH built-in MIC	
Storage	Built-in micro SD card slot, up to 256GB	
Reset	Yes	
Functions		
Remote Monitoring	Web browser /TVT NVR/NVMS2.X/Mobile APP	
Web Browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+	
Online Connection	Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission	
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, P2P, QoS	
Interface Protocol	ONVIF	
Storage	Network remote storage; micro SD card storage	
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, network disconnection, video exception	
Smart Event	Line crossing/region intrusion (human/vehicle classification), abandoned/missing object detection	
General Function	Watermark, IP address filtering, video mask, heartbeat, ANR, cloud upgrade, smart supplement light, corridor pattern, disarming	
PoE	Yes (IEEE802.3af)	
Supplement Light Range	IR range: up to 50 m; white light range: up to 40 m	
Ingress Protection	IP67	

Security	Video encryption, firmware encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP			
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8mm	69m(226ft)	28m(92ft)	14m(46ft)	7m(23ft)
3.6mm	105m(344ft)	42m(138ft)	21m(69ft)	10m(33ft)
2.8~12mm(W)	66m(218ft)	27m(87ft)	13m(44ft)	7m(23ft)
2.8~12mm(T)	204m(669ft)	82m(269ft)	41m(135ft)	20m(66ft)
Others				
Power Supply	DC12V/PoE			
Power Consumption	<9.5W			
Storage Conditions	- 30 °C ~ 65 °C (-22°F~149°F), Humidity: less than 95 % (non-condensing)			
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)			
Dimensions (mm)	217.8 × 80.5 × 80.3			
Weight (net)	Approx. 0.68KG			
Installation	Ceiling mounting; wall mounting			
Certificate	CE, FCC			
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)			

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-9462S4-C-E (D/PE/AW3)	Fixed lens
	TD-9462S4-C-E (D/AZ/PE/AW3)	Motorized lens