TVT

Secure The World With You


CAMERA

TD-9522E3B-A

2MP IR Starlight Dome Network Camera



- 2MP (1920 × 1080)
- H.265+/ H.265/H.264/H.264/ MJPEG coding
- ICR auto switch, true day / night vision
- 20 ~ 30m IR night view distance
- Starlight
- 3D DNR, HWDR, HLC, BLC, Defog, Smart IR and ROI coding
- Support corridor mode
- Support electronic image stabilization
- Support image distortion correction
- 1CH built-in MIC; 1CH audio output and 1CH audio input
- 1CH alarm input and 1CH alarm output
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- Support three streams
- Support mobile surveillance by smart phones & tablet PCs with iOS and Android OS
- Support SMD
- Support NAT function
- Intelligent analytics
- Dual-system backup



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Fax: +86-755-33104777

Web site: http://en.tvt.net.cn

E-mail: overseas@tvt.net.cn

TVT TD-9522E3B-A

2MP IR Starlight Dome Network Camera

SPECIFICATIONS


Model / Specifications	TD-9522E3B-A
Camera	
Image Sensor	1 / 2.8" CMOS
Image Size	1920 × 1080
Electronic Shutter	1 / 3 s ~ 1 / 100000 s
Iris Type	DC Iris
Min. Illumination	0.003lux@F1.3,AGC ON; 0 lux with IR
Lens	2.8~12mm@F1.3, motorized
Field of View	Horizontal: 105°~30° ; Vertical: 55°~16°; Diagonal:123°~35°
Lens Mount	Φ 14
Day& Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
S/N Ratio	⩾50dB
EIS	Yes
Angle Adjustment	Pan: 0°~360°; Tilt:0°~77°; Rotation: 0°~360°
Image	
Video Compression	Main stream: H.265+ / H.265 /H.264+ / H.264 Sub/Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	1080P(1920×1080), 720P(1280×720), D1, VGA(640×480), 640×360, 480×240, CIF
Main Stream	1080P/720P (60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)
Sub Stream	1080P (60Hz:1 ~ 15fps; 50Hz: 1 ~ 12fps) 720P/D1/VGA/640×360/480×240/CIF (60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)
Third Stream	D1/VGA/640×360/CIF/480×240 (60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45 (10/100 Base-T)
Video Output	No
Audio	1CH audio input; 1CH audio output; 1CH built-in MIC
Storage	Built-in micro SD card slot; up to 256GB
Reset	Yes
Alarm	1CH alarm input; 1CH alarm output
Intelligent Analytics	
Intelligent Video Detection (IVD)	Line crossing, region intrusion/entrance/exiting (human/vehicle classification) loitering detection, illegal parking detection, abandoned/ missing object detection
Target Counting	Target counting by line/area, heat map
Exception Detection	Scene change, video blur and abnormal color detection, audio exception
Face Detection	Face detection and face capture
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 4 motor vehicle features and 1 non-motor vehicle feature

DORI Distance

Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	42m(138ft)	17m(56ft)	8m(26ft)	4m(13ft)
2.8~12mm(T)	154m(505ft)	62m(203ft)	31m(102ft)	15m(49ft)

Functions	
Remote Monitoring	Web Browser/NVMS/NVR/mobile APP
Web Browser	Chrome 105.0+/Edge 105.0+/Firefox 121.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	TCP, UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, NAT, QoS, ICMP, IGMP
Interface Protocol	ONVIF
API&SDK	Yes
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, Network disconnection, sensor alarm, audio alarm
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern, disarming, ANR, cloud upgrade
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP/API
PoE	Yes , IEEE802.3af
IR Distance	20 ~ 30 m
Water-proof Grade	No
Others	
Power Supply	DC12V/PoE
Power Consumption	< 7.5W
Storage Conditions	- 10 °C ~ 50 °C(14°F~122°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 10 °C ~ 40 °C (14°F~104°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 121.6 × 95.9
Weight (net)	Approx. 0.38KG
Material	Plastic
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU), and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE MODEL

Available Model	TD-9522E3B-A (D / AZ / PE / AR2)

*All pictures and specifications are for reference only and are subject to change without prior notice.