


CAMERA

TD-9581E3H-A

8MP IR Water-Proof Dome
Network Camera



- H.265+/H.265/H.264+/H.264/MJPEG coding
- Starlight
- Max. resolution: 8MP (3840 × 2160)
- ICR auto switch, true day / night vision
- 20 ~ 30m IR night view distance
- 3D DNR, true WDR, HLC, BLC, Defog, NIR, Smart IR and ROI coding
- Support image distortion correction
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- IP67 & IK10
- Support three streams
- Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- Intelligent analytics
- Support P2P function
- Support dual-system backup



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay
Eco-Technology Park, Nanshan District, Shenzhen, Guangdong
Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777


E-mail: overseas@tvt.net.cn

SPECIFICATIONS

Model	TD-9581E3H-A			
Specifications				
Camera				
Image Sensor	1 / 1.8 "CMOS			
Image Size	3840 × 2160			
Electronic Shutter	1/ 2 s ~ 1 / 100000 s			
Iris Type	Fixed Iris			
Min. Illumination	0.008 lux@F1.6,AGC ON; 0 lux with IR			
Lens	2.8 mm@F1.6, H.FoV: 110°; V.FoV: 57.5°; D.FoV:133.5° 3.6 mm@F1.6, H.FoV: 87.5°; V.FoV:49°; D.FoV:97°			
Focus	Fixed			
Lens Mount	M12			
Day & Night	ICR			
Wide Dynamic Range	120dB			
BLC	Yes			
HLC	Yes			
Defog	Yes			
Digital NR	3D DNR			
S/N Ratio	≥ 50dB			
EIS	Yes			
Angle Adjustment	Pan : 0°~355°, Tilt : 0°~70°, Rotation : 0°~180°			
Image				
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG			
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile			
Resolution	8MP (3840×2160), 6MP (3200×1800),4MP (2688×1520), 2K (2560×1440), 1080P (1920×1080), 720P (1280×720) , D1, VGA (640×480),640×360, CIF, 480×240			
Main Stream	8MP/6MP/4MP/2K/1080P(60Hz : 1~30fps; 50Hz : 1~25fps)			
Sub Stream	1080P(1~15fps)/720P/D1/640 ×360(60Hz:1 ~ 30fps; 50Hz: 1 ~ 25fps)			
Third Stream	720P(1~15fps)/D1/VGA/640 ×360/480 ×240/CIF(60Hz:1~30fps; 50Hz:1~25fps)			
Bit Rate	64 Kbps ~ 12 Mbps			
Bit Rate Type	VBR / CBR			
Audio Compression	G711 A / U			
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser			
ROI	Each ROI to be configured separately			
Interfaces				
Network	RJ 45 10M/100M self-adaptive Ethernet port			
Video Output	No			
Audio	1CH audio input; 1 CH built-in MIC			
Storage	Built-in micro SD card slot; up to 256GB			
Reset	Yes			
Alarm	1CH alarm input; 1CH alarm output			
Intelligent Analytics (Smart Events)				
Smart Event	Line crossing, region intrusion/entrance/exiting, loitering detection, illegal parking detection, abandoned/ missing object detection			
Statistics	Target counting by line/area, heat map			
Exception Detection	Scene change, video blur and abnormal color detection, audio exception			
Face Recognition	Face detection, face capture and face comparison			
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 4 motor vehicle features and 1 non-motor vehicle feature			
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8mm	78.74m(258.33ft)	31.50m(103.34ft)	15.75m(51.67ft)	7.87m(25.82ft)
3.6mm	94.79m(310.99ft)	37.92m(124.40ft)	18.96m(62.20ft)	9.48m(31.10ft)
Functions				
Remote Monitoring	Web Browser/TVT NVMS2.0/NVR/mobile APP			
Web Browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+			

Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, HTTP POST, 802.1x, UPnP, HTTPS, P2P, QoS
Interface Protocol	ONVIF
API&SDK	Yes
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, Network disconnection, sensor alarm
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern, ANR, cloud upgrade
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP
PoE	Yes, IEEE802.3af
IR Distance	20 ~30 m
Ingress Protection	IP67&IK10
Others	
Power Supply	DC12V/PoE
Power Consumption	< 9W
Storage Conditions	- 30 °C ~ 65 °C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Ø 119 × 87.8
Weight (net)	Approx. 0.65KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH(EC1907/2006)


DIMENSIONS



AVAILABLE MODEL

Available Model	TD-9581E3H-A(D/PE/AR2)
-----------------	------------------------

AVAILABLE ACCESSORIES



TD-YXH0101B



TD-YZJ0203



TD-YZJ0701A



TD-YXH0101B
+TD-YZJ0810



TD-YZJ0215



TD-YXH0101B+
TD-YZJ0406+
TD-YZJ0501



TD-YXH0101B+
TD-YZJ0406+
TD-YZJ0601



TD-YXH0101B
+TD-YZJ0406



TD-YZJ0215+
TD-YZJ0501



TD-YZJ0215+
TD-YZJ0601