TVT


Secure The World With You

TD-9563S4-C

6MP IR Water-proof Dome Network Camera



- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution: 6MP (3200 × 1800)
- Auto day/night switch
- 3D DNR, HWDR, HLC, BLC, etc.
- ROI coding
- 30~50m IR view distance
- DC12V/PoE power supply
- IP 67 & IK10 ingress protection
- Support three streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support NAT function
- Support SMD
- Support line crossing detection, region intrusion detection, abandoned/missing object detection, video exception detection
- Dual-system backup



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Fax: +86-755-33104777

Web site: http://en.tvt.net.cn

E-mail: overseas@tvt.net.cn

TVT TD-9563S4-C

6MP IR Water-Proof Dome Network Camera

SPECIFICATIONS

Model / Specifications	TD-9563S4-C
Camera	
Image Sensor	1 / 2.5 "CMOS
Image Size	3200×1800
Electronic Shutter	1 / 4 s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.008 lux @F1.6, AGC ON; 0 lux with IR on
Lens	2.8~12mm@F1.6, Horizontal FoV: 108°~36°; Vertical FoV: 57°~20°; Diagonal FoV: 129°~42°
Focus	Motorized
Lens Mount	Ø14
Day&Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Digital NR	Yes
S/N Ratio	⩾50dB
Angle Adjustment	Pan: 0°~345°; Tilt: 0°~77°; Rotation: 0°~345°
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub /Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	6MP (3200×1800), 4MP(2688×1520), 2K(2560×1440), 1080P(1920×1080), 720P (1280×720), D1, VGA (640×480), 480×240, CIF
Main Stream	6MP(1~20fps) /4MP/2K/1080P (60Hz: 1~30fps; 50Hz: 1~25fps)
Sub Stream	1080P (60Hz:1~15fps; 50Hz:1~12fps)/ 720P/D1/VGA/480×240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream	D1/480× 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	64 Kbps ~8Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
Audio Compression	G711A/U
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45 (10/100 Base-T)
Video Output	No
Audio	1CH audio input; 1CH built-in MIC
Storage	Built-in micro SD card slot, up to 256GB
Reset	Yes
Functions	
Remote Monitoring	Web browser /NVR/NVMS/Mobile APP
Web Browser	Chrome 105.0+/Edge 105.0+/Firefox 121.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, NAT, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
API&SDK	Yes
Smart Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, network disconnection, video exception
Intelligent Video Detection (IVD)	Line crossing/region intrusion (human/vehicle classification), abandoned/missing object detection
General Function	Watermark, IP address filtering, video mask, heartbeat, ANR, cloud upgrade, smart supplement light, corridor pattern, disarming
PoE	Yes (IEEE802.3af)
IR Distance	30 ~ 50 m
Ingress Protection	IP67&IK10
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP/API


*When HWDR function is enabled, the main/sub/third stream supports up to 20fps (except for the 1080P sub stream).

DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	66m(218ft)	27m(87ft)	13m(44ft)	7m(23ft)
2.8~12mm(T)	204m(669ft)	82m(269ft)	41m(135ft)	20m(66ft)

Others	
Power Supply	DC12V/PoE
Power Consumption	DC12V: < 6.8W; PoE: <8.5W
Storage Conditions	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 141 × 100
Weight (net)	Approx. 0.88KG
Material	Aluminum alloy body
Installation	Ceiling mounting; wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), and REACH(EC1907/2006)

DIMENSIONS

Unit: mm



AVAILABLE ACCESSORIES



TD-YXH0207 TD-YZJ0701B TD-YZJ0216 TD-YXH0207+ TD-YZJ0407 TD-YXH0207+ TD-YZJ0811



TD-YXH0207+ TD-YZJ0407+ TD-YZJ0501 TD-YXH0207+ TD-YZJ0407+ TD-YZJ0601 TD-YZJ0216+ TD-YZJ0501 TD-YZJ0216+ TD-YZJ0601

AVAILABLE MODEL

Available Model	TD-9563S4-C(D/AZ/PE/AR3)

*All pictures and specifications are for reference only and are subject to change without prior notice.