TVT


Secure The World With You

TD-9541S5A

4MP Dual Illumination Water-proof Dome Network Camera



- H.265S /H.265+ /H.265 /H.264S /H.264+ /H.264/MJPEG coding
- Max. resolution:4MP (2688 × 1520)
- 3D DNR, HWDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- 20~30m white light view distance; 20~30m IR view distance
- DC12V/PoE power supply
- IP 67 & IK10 ingress protection
- Support three streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support P2P function
- Support SMD
- Support line crossing detection, region intrusion detection, abandoned/missing object detection
- Dual system backup



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Fax: +86-755-33104777

Web site: http://en.tvt.net.cn

E-mail: overseas@tvt.net.cn

TVT TD-9541S5A

4MP Dual Illumination Dome Network Camera

SPECIFICATIONS


Model / Specifications	TD-9541S5A
Camera	
Image Sensor	1 / 3 "CMOS
Image Size	2688×1520
Electronic Shutter	1/3s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.005 lux @F1.6, AGC ON; 0 lux with illumination on
Lens	2.8mm@F1.6, Horizontal FoV: 104°;Vertical FoV:57°;Diagonal FoV:120° 3.6mm@F1.6, Horizontal FoV:82°;Vertical FoV:45°;Diagonal FoV:95°
Focus	Fixed
Lens Mount	M12
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Digital NR	Yes
S/N Ratio	⩾50dB
Angle Adjustment	Pan: 0°~355°; Tilt:0°~70°;Rotation: 0°~180°
Image	
Video Compression	Main stream: H.265S / H.265+ / H.265 / H.264S /H.264+ / H.264 Sub/Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	4MP (2688 × 1520), 2K (2560 × 1440), 1080P (1920 × 1080), 720P (1280 × 720), D1, VGA (640× 480), 640× 360, 480× 240, CIF
Main Stream	4MP/2K/1080P (60Hz: 1~30fps; 50Hz: 1~25fps)
Sub Stream	720P/D1/VGA/640× 360 /480× 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
Third Stream	D1/640× 360 /VGA/480× 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	32Kbps ~ 6 Mbps
Bit Rate Type	VBR / CBR
SVC	Yes
Stream Smoothing	Yes
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
Audio Compression	G711A/U
ROI	8 regions; each ROI to be configured separately
Interfaces	
Network	RJ 45 (10/100 Base-T)
Video Output	No
Audio	1CH audio input; 1CH built-in MIC
Storage	Built-in micro SD card slot, up to 512GB
Reset	Yes
Functions	
Remote Monitoring	Web browser /NVR/NVMS/Mobile APP
Web Browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, P2P, QoS
Interface Protocol	ONVIF
API&SDK	Yes
Storage	Network remote storage; micro SD card storage
Alarm	Motion detection, SMD, SD card error, SD card full, IP address conflict, network disconnection, white light alarm triggered by smart events
Smart Event	Line crossing/region intrusion (human/vehicle classification), abandoned/missing object detection
Exception Detection	Scene change, video blur and abnormal color detection, audio exception
General Function	Watermark, IP address filtering, video mask, heartbeat, ANR, cloud upgrade, smart supplement light, corridor pattern, disarming
PoE	Yes (IEEE802.3af)
Supplement Light Range	IR range: 20 ~ 30 m; white light range:20 ~ 30 m
Ingress Protection	IP 67 & IK10

Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and token authentication for HTTP/RTSP

DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8mm	56m(184ft)	22m(73ft)	11m(37ft)	6m(18ft)
3.6mm	68m(224ft)	27m(90ft)	14m(45ft)	7m(22ft)

Others	
Power Supply	DC12V/PoE
Power Consumption	DC12V: max. 4.6W; PoE: max. 6W
Storage Conditions	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Operating Conditions	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Ø 119 × 87.8
Weight (net)	Approx. 0.605KG
Installation	Ceiling mounting; wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE ACCESSORIES


TD-YXH0101B


TD-YZJ0203


TD-YZJ0701A


TD-YXH0101B +TD-YZJ0810


TD-YZJ0215


TD-YXH0101B+ TD-YZJ0406+ TD-YZJ0501


TD-YXH0101B+ TD-YZJ0406+ TD-YZJ0601


TD-YXH0101B +TD-YZJ0406


TD-YZJ0215+ TD-YZJ0501


TD-YZJ0215+ TD-YZJ0601

AVAILABLE MODEL

Available Model	TD-9541S5A(D/PE/AW2)

*All pictures and specifications are for reference only and are subject to change without prior notice.